

DATA SHEET 04600.000.39000

## Folajet Transfer ST

A top coated heat transfer paper for high resolution photographic poster prints, presentations and exhibition images that can be transferred onto fabric and cloth banners. Print the image in reverse and then heat transfer with either a Hot laminator or heat press onto cotton based fabrics.

### Printing Systems



### Rolls

Art.Number	Width (mm)	Length (m)
04600.000.39000	914	20

### Technical data

#### Characteristic



- Heat-Press activation
- High resolution
- No bleeding
- Instant dry

#### Finish

- Transfer paper

#### Specifications

Coating Printsides	Ink Jet
Width (inch)	36

Width (mm)	914
Printside	White side
Length (ft)	65.62
Length (m)	20
Backside	Release paper with printed grid
Base Material	Transfer paper
Packing quantity	1

### **Compatibility**

- Suitable for most Ink Jet plotters using dye- or pigmented inks
- Not compatible with oil and solvent based systems.

### **Handling**

- Between 15-30°C and 30-70% r.h.
- Print side = matt white side
- A preconditioning period of 24 hours within the printing environment is recommended.
- Ink Load: approx. 260 - 300% (may vary according to ink system and RIP calibration).
- Avoid fingerprints on printing side.

### **Storage**

- Unopened in original packaging storage time is 1 year after shipment (under recommended storage conditions).
- Store in a cool and dry place at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.

### **Product liability clause**

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.