

DATA SHEET 20146.125.39200

Folajet Backlit

Folajet Backlit is a single matt coated polyester film for photorealistic prints to be displayed in backlit frames and advertisement panels. Recommended for indoor use, front & back print compatible.

Printing Systems



Rolls

Art.Number	Width (mm)	Length (m)	Nominal thickness (mm)
20146.125.39200	0.125	914	30

Technical data

Characteristic

- Brilliant, true colour reproduction with or without back lighting
- Suitable for dye inks
- Can be used in front and back print mode (right reading resp. mirror prints)
- Suitable for piezo Ink Jet printer
- Suitable for pigment inks which offers improved light stability
- Suitable for thermal Ink Jet printer
- Good ink absorption
- Super sharp edge definition
- High whiteness for excellent contrast
- Fast dry

Finish

- Translucent matt

Specifications

Coating Printsideside	Ink Jet
Width (inch)	36
Width (mm)	914
Printsideside	Matt side
Length (ft)	98.43
Length (m)	30
Nominal thickness (mil)	5
Nominal thickness (mm)	0.125
Backside	Glossy side
Base Material	Polyester film
Packing quantity	1 roll

Compatibility

- Suitable for most Ink Jet plotters using dye- or pigmented inks

Handling

- Between 15-30°C and 30-70% r.h.
- Printer Mode: photo quality, coated paper, o.e.
- A preconditioning period of 24 hours within the printing environment is recommended.
- For Outdoor Use, laminating is recommended.
- Ink Load: approx. 260 - 300% (may vary according to ink system and RIP calibration).
- Lamination :cold or heat lamination. For outdoor application lamination is recommended. Before laminating let the prints dry for minimum 2 hours.

Storage

- Once packaging is opened, store at a room temperature of 15 - 25°C and at a humidity of 30 - 60 %
- Shelf life 1 year after delivery (under above storage conditions)

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.