

DATA SHEET 22112.360.30500

SI 112

Highly white rigid vinyl film with high opacity, B1-certified. Suitable for pop-up-displays, poster, PoS and exhibition displays.

Printing Systems



Rolls

Art.Number	Width (mm)	Thickness	Length (m)
22112.360.39000	914	0.360 mm	20
22112.360.30500	1067	0.360 mm	20

Technical data

Characteristic

- High brilliance of colours
- Flame retardant, tested and certified according to DIN 4102 - 1 (fire protection B1)
- Good scratch resistance
- High opacity
- Can be laminated right to the edges
- Low-reflective printing surface

Finish

- White matt

Specifications

Coating Printsides	microporous coating
Width (mm)	1067
Thickness	0.360 mm
Core Diameter	76 mm

Length (m)	20
Base Material	rigid vinyl
Packing quantity	1 roll

Compatibility

- Suitable for most Ink Jet plotters using dye- or pigmented inks

Handling

- If dye inks are used, must be laminated indoor and outdoor to improve light-fastness and smudge-proofness.
- It is necessary to protect the surface if it is subject over a long time to abrasion or any other mechanical influences, to dirt or humidity. The lamination can be done right to the edges or over the edges. The user should check before using what is more appropriate.
- We recommend to use self-adhesive laminating foils for cold lamination.

Storage

- Shelf life: 1 year after delivery
- After printing the remaining roll must be removed from the plotter and stored in its closed original packing in a cool and dry environment.

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.