

DATA SHEET 29640.100.44100

BG-64

Coating suitable for most mono laser printers. This has one smooth side for easy feeding, and a rougher side for printing.

Printing Systems



Formats

Art.Number	Format	Nominal thickness (mm)	Packing quantity
29640.100.44100	A4	0.100	50
29640.100.43100	A3	0.100	50

Technical data

Characteristic

- Excellent runnability
- Good flatness
- Excellent toner bonding
- Heat resistant

Finish

- Clear transparent

Specifications

Coating Printsideside	Laser printer mono
Width (inch)	8.27
Width (mm)	210
Printside	Rougher side
Format	A4
Length (inch)	11.69

Length (mm)	297
Nominal thickness (mil)	4
Nominal thickness (mm)	0.100
Backside	Glossy side
Base Material	Polyester film
Packing quantity	50

Compatibility

- For use on most Mono Laser Printers

Handling

- Please follow the handling instructions supplied with this product as well as the machine manufacturers manual.
- Avoid moisture and fingerprints.

Storage

- Once packaging is opened, store at a room temperature of 15 - 25°C and at a humidity of 30 - 60%.
- Shelf life 1 year after delivery (under recommended storage conditions)
- Store in a cool and dry place

Product liability clause

The foregoing information and any consulting provided by us in terms of application engineering shall be given to our best knowledge, but shall not be considered binding information neither with regard to any third party industrial property rights. Any such consulting shall not relieve you from your own review of our current consulting information as to their suitability for the intended procedures and applications. It is the users responsibility to determine the suitability for his/her own use and application and test through the complete production process to ensure the product is fully suitable for the intended use, since conditions of use are beyond our control. The sale of our products shall be subject to our current General Terms and Conditions. We reserve the right to make changes that serve to improve the product.